

DILUENTE SINTETICO 4555

Rev. 04 of 03/27/2012

P. 1 of 1

Technical Data Sheet No. 0207931800

Denomination	DILUENTE SINTETICO 4555
Description	Synthetic Thinner
Product details	Special synthetic thinner used for the dilution of synthetic enamels, applied by spray, or special chlorinated-rubber resin based products (Eliover 073 coating for swimming pools), applied also by roller or brush, as well as a wash thinner for said installations and tools. It is formulated with pure raw materials.
VOC Classification (Directive 2004/42/CE)	Not intended for uses contained in Directive 2004/42 / EC "Thinner"
Available sizes	5 liters
Storage	<ul style="list-style-type: none">Keep container tightly closed in a dry, cool placeStorage temperature: up to 5°C / below 35°CShelf life: 36 months under optimal temperature and R.H. (relative humidity) conditionsAvoid the accumulation of electrostatic charges. Keep the containers closed in a well-ventilated place. The vapors can ignite causing explosions, therefore it is necessary to avoid the accumulation keeping windows and doors open and ensuring cross ventilation. Keep away from sources of heat, sparks or naked flames; do not smoke or use matches or lighters.Open the container carefully because it may be under pressure.
Safety standards	<p>The product is classified as dangerous according to the provisions of Directives 67/548/EEC and 1999/45/EC and/or Regulation (EC) 1272/2008 (CLP) (and their subsequent amendments and adjustments). The product therefore requires a Safety Data Sheet in accordance with the provisions of Regulation (EC) 1907/2006 and subsequent amendments.</p> <p>Any additional information regarding risks to health and/or the environment is reported in the sec. 11 and 12 of this sheet.</p> <p>Hazard Statements: Xn-N</p> <p>R-Phrases: 10-20/21-37/38-51/53-65-66</p>

Technical features	Laboratory data observed at 20°C and 65% R.H.
Binder nature	Mix of aromatic solvents
Specific weight (during packaging)	835 ÷ 845 gr/liter
Appearance	Colourless liquid
Flammability in °C	from > 21 to < 55

THIS INFORMATION IS BASED ON THE BEST TECHNICAL KNOWLEDGE IN OUR POSSESSION AND IT IS BELIEVED CORRECT ON THE DATE OF ISSUE OF THIS TECHNICAL DATA SHEET. THE RECOMMENDATIONS AND SUGGESTIONS SET FORTH ABOVE DO NOT REPRESENT ANY WARRANTY BECAUSE THE CONDITIONS OF EMPLOYMENT BY CONSUMERS ARE NOT UNDER OUR DIRECT CONTROL. FOR FURTHER INFORMATION, DO NOT HESITATE TO CONTACT OUR TECHNICAL TEAM.

