

DILUENTE NITRO SPECIAL

Rev. 03 of 04/02/2009 P. 1 of 1
Technical Data Sheet No. 0506931120

Denomination	DILUENTE NITRO SPECIAL
Description	Nitro thinner
Product details	Nitro anti-fog thinner, particularly indicated for the dilution of fast-drying and compatible paint products. The product is applicable by spray. It is formulated with pure raw materials.
VOC Classification (Directive 2004/42/CE)	Not intended for uses contained in Directive 2004/42 / EC “Thinner”
Available sizes	25 liters - 5 liters - 1 liter
Storage	<ul style="list-style-type: none">Keep container tightly closed in a dry, cool placeStorage temperature: up to 5°C / below 35°CShelf life: 36 months under optimal temperature and R.H. (relative humidity) conditionsAvoid the accumulation of electrostatic charges. Keep the containers closed in a well-ventilated place. The vapors can ignite causing explosions, therefore it is necessary to avoid the accumulation keeping windows and doors open and ensuring cross ventilation. Keep away from sources of heat, sparks or naked flames; do not smoke or use matches or lighters. Open the container carefully because it may be under pressure.
Safety standards	<p>The product is classified as dangerous according to the provisions of Directives 67/548/EEC and 1999/45/EC (and their subsequent amendments and adjustments). The product therefore requires labelling and a Safety Data Sheet in accordance with the provisions of Regulation 1991/155/CE and subsequent amendments.</p> <p>Keep container tightly closed and inverted in a cool place, away from sources of heat. Empty containers or containers with slight film traces of dried residual product must be disposed of in accordance with local requirements.</p> <p>For further information, reference should be made to the related Material Safety Data Sheet.</p>

Technical features	Laboratory data observed at 20°C and 65% R.H.
Binder nature	Mixture of aromatic - oxygenated solvents
Specific weight (during packaging)	880 ÷ 890 gr/liter
Appearance	Colourless liquid with a characteristic smell
Flammability in °C	> 21°C

THIS INFORMATION IS BASED ON THE BEST TECHNICAL KNOWLEDGE IN OUR POSSESSION AND IT IS BELIEVED CORRECT ON THE DATE OF ISSUE OF THIS TECHNICAL DATA SHEET. THE RECOMMENDATIONS AND SUGGESTIONS SET FORTH ABOVE DO NOT REPRESENT ANY WARRANTY BECAUSE THE CONDITIONS OF EMPLOYMENT BY CONSUMERS ARE NOT UNDER OUR DIRECT CONTROL. FOR FURTHER INFORMATION, DO NOT HESITATE TO CONTACT OUR TECHNICAL TEAM.

