

ELIOCRYL ENAMEL SATINATA

Rev. 05 of 06/12/2015

P. 1 of 2

Technical Data Sheet No. 2211021219

Denomination	ELIOCRYL ENAMEL SATINATA
Description	Multifunctional Satin Enamel Paint for Extended Surfaces
Product Details	Stain-resistant, water-dilutable, acrylic enamel paint for indoor and outdoor applications. An important feature is multifunctionality, that is the ability of the product to easily anchor on almost all types of masonry, plaster, glass or metal substrates, after the application of adequate primers. It is advisable to use it with a low-thickness short-nap roller, thus obtaining a smooth and homogeneous surface with a pleasant aesthetic and decorative effect.
VOC Classification (Directive 2004/42/EC)	Interior/Exterior Trim and Cladding Paints for Wood, Metal or Plastic EU limit value for this product (cat. A/d): 150 g/l (2007), 130 g/l (2010) This product contains max. 130 g/l VOC
Surface Preparation & Application	NEW SUBSTRATES Interiors: Apply a layer of Eliofond Acrilico water-based fixative, after adequate preparation of the substrate (filling with Supermuralstucco paste filler). Exteriors: Brush carefully, removing any fragments of inconsistent plaster. Level any imperfections with an adequate mortar and complete surface preparation with Eliofond Acrilico. In the case of very crumbling surfaces, we recommend the use of Eliowall Solvent-Based Primer. PAINTED SUBSTRATES Interiors: Remove any trace of old poorly anchored or peeling paint. Cover up any surface imperfections with a suitable quick-setting powder filler (Stuck 84) for cracks and deep holes, and with paste filler (Supermuralstucco) for superficial defects and/or total fillings. Apply a layer of Eliofond Acrilico water-based fixative. Exteriors: Brush carefully removing any parts of poorly anchored old paint, ensuring the surface is clean from dust and dirt. Proceed in the same way as for new substrates, using only Eliowall Solvent-Based Primer.
Practical Advices	Room Temperature: Min. 10°C / Max. 35°C Relative Humidity: Min. 35% / Max. 85% Substrate Conditions: Dry
Available Sizes	White..... 13 liters - 4 liters - 0,750 liters
Storage	<ul style="list-style-type: none">Keep container tightly closed in a dry, cool place.Storage Temperature: up to 5°C / below 40°C.Shelf Life: 24 months under optimal temperature and R.H. conditions.
Safety Standards	Product labeled according to Regulation 1272/2008 (CLP). For further information, reference should be made to the related Material Safety Data Sheet. Empty containers or containers with slight film traces of dried residual product must be disposed of in accordance with local requirements.

ELIOCRYL ENAMEL SATINATA



Technical Features	Laboratory Data @ 20°C (68°F), 65% R.H.
Vehicle Type	Acrylic Copolymer
Specific Weight (during Packaging)	1.200 ÷ 1.220 gr/liter
% Solids	By Weight: 44,4 % ± 1 By Volume: 32,0 % ± 1
Color	White
Viscosity Brookfield RVT at 20°C and 20 rpm	6.000 ÷ 11.000 cps
Flash Point	None
pH after Storage	8,5
Components	One
Dilution (V/V) - Roller	33 %
Dilution (V/V) - Brush	50 %
Thin With	Water
Tools	Roller; Brush
Dry Film Total Thickness (Contrast Ratio: Hp ≥ 98)	40 µm
Coverage at Recommended Film Thickness	8,5 m ² /liter
Dry to Touch	2 ÷ 3 hours
Dry to Handle	5 ÷ 6 hours
Dry to Recoat	Min. 24 hours – Max. N/A
Dry Film Appearance Specular Gloss @ 60°	Semigloss from < 60 to ≥ 30 gloss
Resistance to Washing: N. of Brush Strokes	Excellent ≥ 5000
Alkali Resistance	Alkali resistant. It can be applied on cementitious substrates.
Water Vapor Permeability	Classification: Low Water Vapor Diffusion: from < 15 g/m ² .d (= in 24 h)
Dirt Pick-Up	Δ L --> ≤ 3,0.....Very Low

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED ON OUR RESEARCH AND ARE BELIEVED TO BE ACCURATE, BUT NO WARRANTY, EXPRESS OR IMPLIED, IS MADE OR SHOULD BE INFERRED. PURCHASERS SHOULD TEST THE PRODUCTS TO DETERMINE ACCEPTABLE QUALITY AND SUITABILITY FOR THEIR OWN INTENDED USE. NOTHING CONTAINED HEREIN SHALL BE CONSTRUED TO IMPLY THE NONEXISTENCE OF ANY RELEVANT PATENTS OR TO CONSTITUTE A PERMISSION, INDUCEMENT OR RECOMMENDATION TO PRACTICE ANY INVENTION COVERED BY ANY PATENT, WITHOUT AUTHORITY FROM THE OWNER OF THE PATENT. FOR FURTHER INFORMATION, DO NOT HESITATE TO CONTACT OUR TECHNICAL TEAM.