

# SUPERMURALSTUCCO

Rev. 08 of 06/01/2015 P. 1 of 2  
Technical Data Sheet No. 0409971200

|  |  |
|--|--|
| <b>Denomination</b>                                  | <b>SUPERMURALSTUCCO</b>  |
| <b>Description</b>                                   | Ready-to-Use Putty Filler  |
| <b>Product Details</b>                               | <p>Ready-to-use paste filler for indoor application, characterized by a high filling power and a very high coverage. It allows to fill rough or finished walls and ceilings (concrete, gypsum and wooden interior surfaces) quickly and cleanly; it can be applied only in overlapping thin layers of low thickness, as it is supplied or diluted with a very small amount of water, if necessary. Applicable with a putty knife or a trowel.</p> <p>The ease of use and the smoothness of the product ensure a very low consumption. The product is long-lasting even after being opened; it can be closed and stored, provided that no water and/or extraneous matters are added.</p> <p>This product is also produced in the "Fresh Lemon" version, characterized by the pleasant odor of natural citrus fruits that is released during the drying phase.</p> |
| <b>VOC Classification<br/>(Directive 2004/42/EC)</b> | Not intended for uses contained in Legislative Decree No. 161/2006 (in Italy).   |
| <b>Surface Preparation &amp; Application</b>         | <p><b>NEW SUBSTRATES</b><br/>Apply directly without prior preparation, always at low thicknesses.</p> <p><b>PAINTED SUBSTRATES</b><br/>Apply a coat of ELIOFOND ACRILICO primer, then proceed filling the surface.<br/>Avoid obtaining high thicknesses.</p>   |
| <b>Practical Advices</b>                             | <p>Room Temperature: Min. 5°C / Max. 35°C<br/>Relative Humidity: Min. 35% / Max. 85%<br/>Substrate Conditions: Dry</p>   |
| <b>Available Sizes</b>                               | 20 Kg - 4 Kg - 1 Kg  |
| <b>Storage</b>                                       | <ul style="list-style-type: none"><li>Keep container tightly closed in a dry, cool place.</li><li>Storage Temperature: up to 5°C / below 35°C.</li><li>Shelf Life: 12 months under optimal temperature and R.H. conditions.</li></ul>  |
| <b>Safety Standards</b>                              | <p><b>Product labeled according to Regulation 1272/2008 (CLP).</b></p> <p>For further information, reference should be made to the related Material Safety Data Sheet. Empty containers or containers with slight film traces of dried residual product must be disposed of in accordance with local requirements.</p>   |

# SUPERMURALSTUCCO

Rev. 08 of 06/01/2015 P. 2 of 2  
Technical Data Sheet No. 0409971200

| Technical Features   | Laboratory Data @ 20°C, 65% R.H.                                       |
|----------------------|--|
| Vehicle Type         | Natural Polymers   |
| Specific Weight      | 1.650 ÷ 1.670 gr/liter   |
| Color                | White  |
| Product Appearance   | Paste-Like   |
| Viscosity            | Thixotropic  |
| Flash Point          | None   |
| pH after Storage     | 6,2  |
| Components           | One  |
| Dilution (V/V)       | Ready-to-Use   |
| Thin With            | Water (only for tools cleaning)  |
| Tools                | Putty Knife; Trowel  |
| Coverage             | Variable according to thickness<br>(4 ÷ 6 m <sup>2</sup> /kg per coat) |
| Drying Time          | 2 ÷ 4 hours  |
| Interval for Sanding | 8 ÷ 10 hours   |
| Dry to Recoat        | Min. 12 hours – Max. 10 days   |
| Adherence            | Excellent  |

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED ON OUR RESEARCH AND ARE BELIEVED TO BE ACCURATE, BUT NO WARRANTY, EXPRESS OR IMPLIED, IS MADE OR SHOULD BE INFERRED. PURCHASERS SHOULD TEST THE PRODUCTS TO DETERMINE ACCEPTABLE QUALITY AND SUITABILITY FOR THEIR OWN INTENDED USE. NOTHING CONTAINED HEREIN SHALL BE CONSTRUED TO IMPLY THE NONEXISTENCE OF ANY RELEVANT PATENTS OR TO CONSTITUTE A PERMISSION, INDUCEMENT OR RECOMMENDATION TO PRACTICE ANY INVENTION COVERED BY ANY PATENT, WITHOUT AUTHORITY FROM THE OWNER OF THE PATENT. FOR FURTHER INFORMATION, DO NOT HESITATE TO CONTACT OUR TECHNICAL TEAM.

Giuseppe Di Maria S.p.A. Legal Address: Via Enrico Mattei, 4  
90124 PALERMO (PA)  
Tel. +39.091.391288 Fax. +39.091.391011  
www.dimaria.it E-mail: dimaria@dimaria.it

